

目录/ Contents

闸阀系列/Gate Valve Series	01 ~ 04
截止阀系列/Globe Valve Series	05 ~ 07
止回阀系列/Check Valve Series	08 ~ 09
球阀系列/Ball Valve Series	10 ~ 13
蝶阀系列/Butterfly Valve Series	14 ~ 17
水力阀系列/Hydraulic Valve Series	18 ~ 23
疏水阀系列/Hydrophobic Valve Series	24
过滤器系列/Filter Series	25
铜阀门系列/Copper Valve Series	26
二通阀系列/Two Valve Series	27
安全阀、调节阀系列/Safety Valve, Regulating Valve Series	28
接头、伸缩节、阻火器系列/Joint, Expansion Joint, Flame Arrester Series	29
仪表针型阀、液位计、视镜系列 Meter Needle Type Valve, Liquid Level Gauge, Mirror Series	30 ~ 31
卫生级阀门/Sanitary Valves	32
气动、电动执行附件系列/Pneumatic, Electric Actuator Accessories Series	33 ~ 34
船用阀门系列/Marine valve series	35
旋塞阀系列/Plug Valve Series	36
隔膜阀系列/Diaphragm Valve Series	37
消防专用阀门系列/Fire Control Valve Series	38
冶金阀门系列/Metallurgical Valve Series	39 ~ 42

闸阀系列 Gate Valve Series



中压闸阀 Medium Pressure Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: 1.0~3.2MPa
Nominal Pressure: 1.0~3.2MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



高压闸阀 High Pressure Gate Valve

公称通径: 50~800mm
Nominal diameter: 50~800mm
公称压力: 4.0~32MPa
Nominal Pressure: 4.0~32MPa
适用温度: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



伞齿轮闸阀 Bevel Gear Gate Valve

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: 10.0~25.0MPa
Nominal Pressure: 10.0~25.0MPa
适用温度: $-29^{\circ}\text{C} \sim 600^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 600^{\circ}\text{C}$
适用介质: 水、蒸汽、油品、酸碱
Applicable medium: Water, steam, oil, acid and alkali



电动闸阀 Electric Gate Valve

公称通径: DN50~800mm
Nominal diameter: DN50~800mm
公称压力: PN1.6~6.4MPa
Nominal Pressure: PN1.6~6.4MPa
适用温度: $-29^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



气动闸阀 Pneumatic Gate Valve

公称通径: DN50~800mm
Nominal diameter: DN50~800mm
公称压力: PN1.6~6.4MPa
Nominal Pressure: PN1.6~6.4MPa
适用温度: $-196^{\circ}\text{C} \sim 500^{\circ}\text{C}$
Applicable temperature: $-196^{\circ}\text{C} \sim 500^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



不锈钢闸阀 Stainless Steel Gate Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.6~16.0MPa
Nominal Pressure: PN1.6~16.0MPa
适用温度: $-29^{\circ}\text{C} \sim 200^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 200^{\circ}\text{C}$
适用介质: 水、油品、酸类、碱性
Applicable medium: Water, oil, acid, alkali



低温闸阀 Low Temperature Gate Valve

公称通径: DN40~400mm
Nominal diameter: DN40~400mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-196^{\circ}\text{C} \sim 46^{\circ}\text{C}$
Applicable temperature: $-196^{\circ}\text{C} \sim 46^{\circ}\text{C}$
适用介质: 水、蒸汽、油品、酸类
Applicable medium: Water, steam, oil, acid



日标闸阀 JIS Gate Valve

公称通径: DN1/2"~14"
Nominal diameter: DN1/2"~14"
公称压力: PN150~1000Lb
Nominal Pressure: PN150~1000Lb
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标闸阀
API Gate Valve

公称通径: DN1/2"~14"
Nominal diameter: DN1/2"~14"
公称压力: 150~1000Lb
Nominal Pressure: 150~1000Lb
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



高温高压整体锻钢闸阀
High Pressure And High Temperature Solid Forged Steel Valve

公称通径: DN50~350mm
Nominal diameter: DN50~350mm
公称压力: 1.0~10.0MPa
Nominal Pressure: 1.0~10.0MPa
适用温度: 302.4°C
Applicable temperature: 302.4°C
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



锻钢闸阀
Forged Gate Valve

公称通径: DN3/8"~2"mm
Nominal diameter: DN3/8"~2"mm
公称压力: 150~2500Lb
Nominal Pressure: 150~2500Lb
适用温度: -29°C ~ 425°C
Applicable temperature: -29°C ~ 425°C
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



国标电站闸阀
National Standard Of Power Station Valve

公称通径: DN40~600mm
Nominal diameter: DN40~600mm
公称压力: 1.6~32MPa
Nominal Pressure: 1.6~32MPa
适用温度: -30°C ~ 600°C
Applicable temperature: -30°C ~ 600°C
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



国标波纹式闸阀
GB Corrugated Gate Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: 1.0~10.0MPa
Nominal Pressure: 1.0~10.0MPa
适用温度: -26°C ~ 350°C
Applicable temperature: -26°C ~ 350°C
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标波纹式闸阀
API Corrugated Gate Valve

公称通径: DN1/2"~20"
Nominal diameter: DN1/2"~20"
公称压力: 150~900Lb
Nominal Pressure: 150~900Lb
适用温度: -26°C ~ 450°C
Applicable temperature: -26°C ~ 450°C
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



不锈钢保温闸阀
Stainless steel Insulation Gate Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: 1.0~10Mpa
Nominal Pressure: 1.0~10Mpa
适用温度: -40°C ~ 425°C
Applicable temperature: -40°C ~ 425°C
适用介质: 水、硝酸、尿素
Applicable medium: Water, nitrate, urea



防盗闸阀
Anti Theft Valve

公称通径: DN40~200mm
Nominal diameter: DN40~200mm
公称压力: 1.0~4.0Mpa
Nominal Pressure: 1.0~4.0Mpa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

闸阀系列 Gate Valve Series



带吹扫孔闸阀 With Purge Holes Gate Valve

公称通径: DN40~1400mm
Nominal diameter: DN40~1400mm
公称压力: 1.0~35.0MPa
Nominal Pressure: 1.0~35.0MPa
适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



陶瓷闸阀 Ceramic Gate Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: 1.0~42.0MPa
Nominal Pressure: 1.0~42.0MPa
适用温度: -40℃~350℃
Applicable temperature: -40℃~350℃
适用介质: 干灰、粉、煤灰及固体颗粒
Applicable medium: Dry ash, fly ash and solid particles



衬氟闸阀 Fluorine-lining Gate Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: 1.6MPa
Nominal Pressure: 1.6MPa
适用温度: -50℃~150℃
Applicable temperature: -50℃~150℃
适用介质: 水、酸性、碱性
Applicable medium: Water, acid, alkali



丝口闸阀 Wire Port Gate Valve

公称通径: DN3/8"-2"
Nominal diameter: DN3/8"-2"
公称压力: 150~600Lb
Nominal Pressure: 150~600Lb
适用温度: 0℃~425℃
Applicable temperature: 0℃~425℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



排渣闸阀 Dregs Gate Valve

公称通径: DN50~500mm
Nominal diameter: DN50~500mm
公称压力: 0.6~6.4MPa
Nominal Pressure: 0.6~6.4MPa
适用温度: -26℃~900℃
Applicable temperature: -26℃~900℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



真空隔离闸板阀 The Vacuum Gate Valve

公称通径: DN50~1000mm
Nominal diameter: DN50~1000mm
公称压力: 1.0~10.0MPa
Nominal Pressure: 1.0~10.0MPa
适用温度: -29℃~200℃
Applicable temperature: -29℃~200℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



水封闸阀 Water Seal Gate Valve

公称通径: DN50~500mm
Nominal diameter: DN50~500mm
公称压力: 1.0~16MPa
Nominal Pressure: 1.0~16MPa
适用温度: 0℃~425℃
Applicable temperature: 0℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



带导流孔平板闸阀 With Deflector Flat Gate Valve

公称通径: DN50~1000mm
Nominal diameter: DN50~1000mm
公称压力: 1.6~2.5MPa
Nominal Pressure: 1.6~2.5MPa
适用温度: ≤180℃
Applicable temperature: ≤180℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



刀型闸阀
Knife Gate Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -38℃~425℃
Applicable temperature: -38℃~425℃
适用介质: 水、纸浆
Applicable medium: Water, pulp



螺旋闸阀
Spiral Gate Valve

公称通径: DN40~300mm
Nominal diameter: DN40~300mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -20℃~120℃
Applicable temperature: -20℃~120℃
适用介质: 水、纸浆
Applicable medium: Water, pulp



手动暗杆刀型闸阀
Manual dark bar type knife gate valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -38℃~425℃
Applicable temperature: -38℃~425℃
适用介质: 水、纸浆
Applicable medium: Water, pulp



低压闸阀
Low Pressure Gate Valve

公称通径: DN40~2600mm
Nominal diameter: DN40~2600mm
公称压力: PN0.6~1.0MPa
Nominal Pressure: PN0.6~1.0MPa
适用温度: ≤100℃
Applicable temperature: ≤100℃
适用介质: 水、蒸汽、油品、煤气
Applicable medium: Water, steam, oil, gas



煤气闸阀
Gas Gate Valve

公称通径: DN40~2600mm
Nominal diameter: DN40~2600mm
公称压力: PN0.1MPa
Nominal Pressure: PN0.1MPa
适用温度: ≤100℃
Applicable temperature: ≤100℃
适用介质: 水、蒸汽、油品、煤气
Applicable medium: Water, steam, oil, gas



法兰连接(O型圈密封)暗杆闸阀
Flange Connection (o-ring Seal) Dark Bar Valve

公称通径: DN40~2600mm
Nominal diameter: DN40~2600mm
公称压力: PN0.6~1.0MPa
Nominal Pressure: PN0.6~1.0MPa
适用温度: ≤100℃
Applicable temperature: ≤100℃
适用介质: 水、油品、煤气
Applicable medium: Water, oil, gas



加长杆低压闸阀
The Lengthening Bar Low Pressure Valve

公称通径: DN40~800mm
Nominal diameter: DN40~800mm
公称压力: PN0.6~1.0MPa
Nominal Pressure: PN0.6~1.0MPa
适用温度: -29℃~425℃
Applicable temperature: -29℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



沟槽式软密封闸阀
Groove Type Soft Sealing Gate Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: ≤100℃
Applicable temperature: ≤100℃
适用介质: 水、油品、空气
Applicable medium: Water, oil, air

截止阀系列 Globe Valve Series



法兰柱塞阀
Flange Plunger valve

公称通径: DN50~450mm
Nominal diameter: DN50~450mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: -20℃~280℃
Applicable temperature: -20℃~280℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



铸钢截止阀
Cast Steel Globe Valve

公称通径: DN50~400mm
Nominal diameter: DN50~400mm
公称压力: PN1.6~6.4MPa
Nominal Pressure: PN1.6~6.4MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



高压截止阀
High Pressure Globe Valve

公称通径: DN50~400mm
Nominal diameter: DN50~400mm
公称压力: PN6.4~32MPa
Nominal Pressure: PN6.4~32MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



电动截止阀
Electric Globe Valve

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.6~16MPa
Nominal Pressure: PN1.6~16MPa
适用温度: ≤425℃
Applicable temperature: ≤425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



伞齿轮截止阀
Bevel Gear Globe Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.6~32MPa
Nominal Pressure: PN1.6~32MPa
适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标截止阀
API Globe Valve

公称通径: DN1/4"~16"
Nominal diameter: DN1/4"~16"
公称压力: PN125~3500Lb
Nominal Pressure: PN125~3500Lb
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



电站截止阀
Power Station Globe Valve

公称通径: 2"~12"
Nominal diameter: 2"~12"
公称压力: PN600~2500Lb
Nominal Pressure: PN600~2500Lb
适用温度: ≤570℃
Applicable temperature: ≤570℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



低温截止阀
Low Temperature Globe Valve

公称通径: DN50~400mm
Nominal diameter: DN50~400mm
公称压力: PN1.0~32MPa
Nominal Pressure: PN1.0~32MPa
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



德标波纹管截止阀
DIN Bellows Globe Valve

公称通径: DN50~400mm
Nominal diameter: DN50~400mm
公称压力: PN1.6~10MPa
Nominal Pressure: PN1.6~10MPa
适用温度: -29℃~425℃
Applicable temperature: -29℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



不锈钢截止阀
Stainless Steel Globe Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN1.0~32.0MPa
Nominal Pressure: PN1.0~32.0MPa
适用温度: -25℃~425℃
Applicable temperature: -25℃~425℃
适用介质: 水、蒸汽、油品、酸类
Applicable medium: Water, steam, oil, acid



衬氟截止阀
Fluorine Lining Valve

公称通径: DN40~300mm
Nominal diameter: DN40~300mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -50℃~150℃
Applicable temperature: -50℃~150℃
适用介质: 水、酸性
Applicable medium: Water, acid



法兰锻钢截止阀
Forged steel Globe Valve

公称通径: DN50~50mm
Nominal diameter: DN50~50mm
公称压力: PN1.0~32MPa
Nominal Pressure: PN1.0~32MPa
适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



液化气截止阀
LPG Globe Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN2.5~4.0MPa
Nominal Pressure: PN2.5~4.0MPa
适用温度: -40℃~80℃
Applicable temperature: -40℃~80℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



真空隔离截止阀
The Vacuum Isolation Valve

公称通径: DN50~150mm
Nominal diameter: DN50~150mm
公称压力: PN4.0~10.0MPa
Nominal Pressure: PN4.0~10.0MPa
适用温度: 0℃~425℃
Applicable temperature: 0℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



角式截止阀
The Angle Type Valve

公称通径: DN10~300mm
Nominal diameter: DN10~300mm
公称压力: PN1.6~32MPa
Nominal Pressure: PN1.6~32MPa
适用温度: -26℃~600℃
Applicable temperature: -26℃~600℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



丝口截止阀
Silk Export Cut-off Valve

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: ≤300℃
Applicable temperature: ≤300℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

截止阀系列 Globe Valve Series



夹套保温截止阀
Jacket Insulation Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN2.5~6.4MPa
Nominal Pressure: PN2.5~6.4MPa
适用温度: -29℃~200℃
Applicable temperature: -29℃~200℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



Y型保温截止阀
Y Type Insulation Globe Valve

公称通径: DN40~300mm
Nominal diameter: DN40~300mm
公称压力: PN1.0~10.0MPa
Nominal Pressure: PN1.0~10.0MPa
适用温度: ≤425℃
Applicable temperature: ≤425℃
适用介质: 水、硝酸、尿素
Applicable medium: Water, nitrate, urea



高压电站节流阀
High Power Station Throttle

公称通径: DN100~500mm
Nominal diameter: DN100~500mm
公称压力: PN10.0~32.0MPa
Nominal Pressure: PN10.0~32.0MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



水封截止阀
Seal Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN2.5~4.0MPa
Nominal Pressure: PN2.5~4.0MPa
适用温度: ≤450℃
Applicable temperature: ≤450℃
适用介质: 水、油品、蒸汽
Applicable medium: Water, oil, steam



抗生素截止阀
Antibiotic Stop Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.6~10MPa
Nominal Pressure: PN1.6~10MPa
适用温度: -196℃~200℃
Applicable temperature: -196℃~200℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



法兰节流阀
Flange Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN1.6~16.0MPa
Nominal Pressure: PN1.6~16.0MPa
适用温度: -29℃~121℃
Applicable temperature: -29℃~121℃
适用介质: 水、油品
Applicable medium: Water, oil



多功能截止阀
Multifunctional Valve

公称通径: DN50~400mm
Nominal diameter: DN50~400mm
公称压力: PN0.6~4MPa
Nominal Pressure: PN0.6~4MPa
适用温度: -20℃~150℃
Applicable temperature: -20℃~150℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



不锈钢氧气阀
Stainless Steel Oxygen Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: ≤150℃
Applicable temperature: ≤150℃
适用介质: 氧气、氮气
Applicable medium: Oxygen, nitrogen



国标升降式止回阀
GB Lift Check Valve

公称口径: DN50 ~ 400mm
Nominal diameter: DN50 ~ 400mm
公称压力: PN0.6 ~ 32MPa
Nominal Pressure: PN0.6 ~ 32MPa
适用温度: -26℃ ~ 425℃
Applicable temperature: -26℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



国标旋启式止回阀
GB Swing Check Valve

公称口径: DN50 ~ 1000mm
Nominal diameter: DN50 ~ 1000mm
公称压力: PN0.6 ~ 32MPa
Nominal Pressure: PN0.6 ~ 32MPa
适用温度: -26℃ ~ 425℃
Applicable temperature: -26℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



国标立式止回阀
GB Vertical Check Valve

公称口径: DN40 ~ 300mm
Nominal diameter: DN40 ~ 300mm
公称压力: PN0.6 ~ 32MPa
Nominal Pressure: PN0.6 ~ 32MPa
适用温度: -30℃ ~ 425℃
Applicable temperature: -30℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标旋启式止回阀
API Swing Check Valve

公称口径: DN1/2" ~ 40"
Nominal diameter: DN1/2" ~ 40"
公称压力: PN125 ~ 3500Lb
Nominal Pressure: PN125 ~ 3500Lb
适用温度: -26℃ ~ 425℃
Applicable temperature: -26℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标立式止回阀
API Vertical Check Valve

公称口径: DN1/2" ~ 12"
Nominal diameter: DN1/2" ~ 12"
公称压力: PN150 ~ 900Lb
Nominal Pressure: PN150 ~ 900Lb
适用温度: -26℃ ~ 450℃
Applicable temperature: -26℃ ~ 450℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



对夹式止回阀
Wafer Check Valve

公称口径: DN40 ~ 800mm
Nominal diameter: DN40 ~ 800mm
公称压力: PN0.6 ~ 10.0MPa
Nominal Pressure: PN0.6 ~ 10.0MPa
适用温度: -30℃ ~ 425℃
Applicable temperature: -30℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



耐磨陶瓷排渣止回阀
Wear Ceramics Slagging Check Valve

公称口径: DN40 ~ 800mm
Nominal diameter: DN40 ~ 800mm
公称压力: PN0.6 ~ 32MPa
Nominal Pressure: PN0.6 ~ 32MPa
适用温度: -40℃ ~ 350℃
Applicable temperature: -40℃ ~ 350℃
适用介质: 干灰、粉、煤灰及固体颗粒
Applicable medium: Dry ash, fly ash and solid particles



美标低温锻钢止回阀
API Low Temperature Forged Check Valve

公称口径: DN3/8" ~ 2"
Nominal diameter: DN3/8" ~ 2"
公称压力: PN150 ~ 2500Lb
Nominal Pressure: PN150 ~ 2500Lb
适用温度: -196℃ ~ 425℃
Applicable temperature: -196℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

止回阀系列 Check Valve Series



德标升降式止回阀
Din Lift Check Valve

公称通径: DN1/2" ~ 16"
Nominal diameter: DN1/2" ~ 16"
公称压力: PN125 ~ 3500Lb
Nominal Pressure: PN125 ~ 3500Lb
适用温度: -26℃ ~ 425℃
Applicable temperature: -26℃ ~ 425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



自密封旋启式止回阀
Self Sealing Swing Check Valve

公称通径: DN2" ~ 36"
Nominal diameter: DN2" ~ 36"
公称压力: PN900 ~ 2500Lb
Nominal Pressure: PN900 ~ 2500Lb
适用温度: ≤425℃
Applicable temperature: ≤425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



衬氟止回阀
Fluorine Lining Valve

公称通径: DN40~300mm
Nominal diameter: DN40~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: -50℃~150℃
Applicable temperature: -50℃~150℃
适用介质: 水、酸性
Applicable medium: Water, acid



空排止回阀
Air Check Valve

公称通径: DN125~175mm
Nominal diameter: DN125~175mm
公称压力: PN2.0MPa
Nominal Pressure: PN2.0MPa
适用温度: ≤160℃
Applicable temperature: ≤160℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



高温高压锻钢水压试验阀
High Temperature And High Pressure Forged Steel Pressure Test Valve

公称通径: DN350 ~ 850mm
Nominal diameter: DN350 ~ 850mm
公称压力: PN4.0 ~ 6.4MPa
Nominal Pressure: PN4.0 ~ 6.4MPa
适用温度: 575℃
Applicable temperature: 575℃
适用介质: 水、蒸汽、气体、石油
Applicable medium: Water, steam, gas, oil



保温止回阀
Insulation Check Valve

公称通径: DN50 ~ 300mm
Nominal diameter: DN50 ~ 300mm
公称压力: PN1.6 ~ 16.0MPa
Nominal Pressure: PN1.6 ~ 16.0MPa
适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃
适用介质: 水、油品、蒸汽
Applicable medium: Water, oil, steam



排渣止回阀
Discharge Check Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.6~6.4MPa
Nominal Pressure: PN1.6~6.4MPa
适用温度: ≤425℃
Applicable temperature: ≤425℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



底阀
Bottom Valve

公称通径: DN50 ~ 800mm
Nominal diameter: DN50 ~ 800mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: 0℃~100℃
Applicable temperature: 0℃~100℃
适用介质: 水、油品
Applicable medium: Water, oil



国标浮动球阀
GB Floating Ball Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm

公称压力: PN0.6~16MPa
Nominal Pressure: PN0.6~16MPa

适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃

适用介质: 水、蒸汽、油品、酸类
Applicable medium: Water, steam, oil, acid



美标浮动球阀
API Floating Ball Valve

公称通径: DN1/2"~14"
Nominal diameter: DN1/2"~14"

公称压力: PN150~1000Lb
Nominal Pressure: PN150~1000Lb

适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃

适用介质: 水、硝酸、醋酸类
Applicable medium: Water, nitric acid, acetic acid



日标浮动球阀
JIS Floating Ball Valve

公称通径: DN1/2"~8"
Nominal diameter: DN1/2"~8"

公称压力: PN150~600Lb
Nominal Pressure: PN150~600Lb

适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃

适用介质: 水、蒸汽、油品、酸类
Applicable medium: Water, steam, oil, acid



平台球阀
Platform Ball Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm

公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa

适用温度: ≤280℃
Applicable temperature: ≤280℃

适用介质: 水、蒸汽、油品、酸类
Applicable medium: Water, steam, oil, acid



国标固定球阀
GB Fixed Ball Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm

公称压力: PN1.6~10.0MPa
Nominal Pressure: PN1.6~10.0MPa

适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃

适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标固定球阀
API Fixed Ball Valve

公称通径: DN3/8"~8"
Nominal diameter: DN3/8"~8"

公称压力: PN125~900Lb
Nominal Pressure: PN125~900Lb

适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃

适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



轨道球阀
Track Ball Valve

公称通径: DN1"~28"
Nominal diameter: DN1"~28"

公称压力: PN150~1500Lb
Nominal Pressure: PN150~1500Lb

适用温度: -26℃~600℃
Applicable temperature: -26℃~600℃

适用介质: 水、油、天然气
Applicable medium: Water, oil, natural gas



高压锻钢球阀
High Forged Ball Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm

公称压力: PN16~320MPa
Nominal Pressure: PN16~320MPa

适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃

适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

球阀系列 Ball Valve Series



顶装式球阀
Top Mounted Ball Valve

公称通径: DN2"~24"
Nominal diameter: DN2"~24"
公称压力: PN300~1500Lb
Nominal Pressure: PN300~1500Lb
适用温度: -196℃~550℃
Applicable temperature: -196℃~550℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



衬氟球阀
Lined Ball Valve

公称通径: DN50~250mm
Nominal diameter: DN50~250mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: -50℃~150℃
Applicable temperature: -50℃~150℃
适用介质: 水、酸性
Applicable medium: Water, acid



衬氟放料球阀
Lined Discharge Ball Valve

公称通径: DN25~100mm
Nominal diameter: DN25~100mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -50℃~150℃
Applicable temperature: -50℃~150℃
适用介质: 水、硫酸、盐酸
Applicable medium: Water, sulfuric acid, hydrochloric acid



四通球阀
Four-way Ball Valve

公称通径: DN40~200mm
Nominal diameter: DN40~200mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -26℃~425℃
Applicable temperature: -26℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



全焊接球阀
Full Welded Ball Valve

公称通径: DN2"~48"
Nominal diameter: DN2"~48"
公称压力: PN150~1500Lb
Nominal Pressure: PN150~1500Lb
适用温度: -29℃~425℃
Applicable temperature: -29℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



埋地球阀
Buried Ball Valve

公称通径: DN2"~48"
Nominal diameter: DN2"~48"
公称压力: PN150~1500Lb
Nominal Pressure: PN150~1500Lb
适用温度: -29℃~150℃
Applicable temperature: -29℃~150℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



陶瓷球阀
Ceramic Ball Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN1.0~6.4MPa
Nominal Pressure: PN1.0~6.4MPa
适用温度: -40~350℃
Applicable temperature: -40~350℃
适用介质: 煤粉、煤渣、粉状颗粒
Applicable medium: Coal, slag, powder particles



防盗球阀
Security Ball Valve

公称通径: DN80~300mm
Nominal diameter: DN80~300mm
公称压力: PN1.6~10MPa
Nominal Pressure: PN1.6~10MPa
适用温度: ≤425℃
Applicable temperature: ≤425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



一体式球阀
One Type Ball

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



不锈钢薄型球阀
Thin Stainless Steel Ball Valve

公称通径: DN15~150mm
Nominal diameter: DN15~150mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



一片式球阀
A Ball Valve

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



二片式球阀
Two-piece Ball Valve

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、油品
Applicable medium: Water, oil



三片式球阀
Three-piece Ball Valve

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、油品
Applicable medium: Water, oil



防爆气动球阀
Explosion-proof Pneumatic Ball Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.4~0.6MPa
Nominal Pressure: PN0.4~0.6MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



槽车球阀
Explosion-proof Pneumatic Ball Valve

公称通径: DN25~80mm
Nominal diameter: DN25~80mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Applicable temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
适用介质: 石油、天然气、液氨
Applicable medium: Petroleum, natural gas, liquid ammonia



氧气球阀
Oxygen Ball Valve

公称通径: DN50~200mm
Nominal diameter: DN50~200mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: $-20^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \sim 150^{\circ}\text{C}$
适用介质: 水、氧气
Applicable medium: Water, oxygen

球阀系列 Ball Valve Series



清管阀
Pig Valve

公称通径: DN100 ~ 250mm
Nominal diameter: DN100 ~ 250mm
公称压力: PN 1.6 ~ 10MPa
Nominal Pressure: PN 1.6 ~ 10MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



气动卸灰球阀
Pneumatic Ash Unloading Valve

公称通径: DN50 ~ 300mm
Nominal diameter: DN50 ~ 300mm
公称压力: PN1.6 ~ 10MPa
Nominal Pressure: PN1.6 ~ 10MPa
适用温度: $-29^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 水、油
Applicable medium: Water, oil



V型球阀
V-Ball Valve

公称通径: DN1" ~ 20"
Nominal diameter: DN1" ~ 20"
公称压力: PN150Lb
Nominal Pressure: PN150Lb
适用温度: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-30^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



偏心半球阀
Eccentric Half Ball Valve

公称通径: DN50 ~ 300mm
Nominal diameter: DN50 ~ 300mm
公称压力: PN0.6 ~ 4.0Mpa
Nominal Pressure: PN0.6 ~ 4.0Mpa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、油品、粉尘颗粒物
Applicable medium: Water, oil, dust particles




水电进水球阀
Water Inlet Valve

公称通径: DN50 ~ 300mm
Nominal diameter: DN50 ~ 300mm
公称压力: PN0.6 ~ 4.0MPa
Nominal Pressure: PN0.6 ~ 4.0MPa
适用温度: $-29^{\circ}\text{C} \sim 200^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 200^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



高压球阀
High Pressure Ball Valve

公称通径: DN40 ~ 150mm
Nominal diameter: DN40 ~ 150mm
公称压力: PN1.6 ~ 32.0mpa
Nominal Pressure: PN1.6 ~ 32.0mpa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



沥青球阀
Asphalt Valve

公称通径: DN50 ~ 300mm
Nominal diameter: DN50 ~ 300mm
公称压力: PN0.6 ~ 6.4Mpa
Nominal Pressure: PN0.6 ~ 6.4Mpa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



全塑法兰球阀
Full Plastic Flange Ball Valve

公称通径: DN40 ~ 300mm
Nominal diameter: DN40 ~ 300mm
公称压力: PN1.6 ~ 2.5Mpa
Nominal Pressure: PN1.6 ~ 2.5Mpa
适用温度: $-10^{\circ}\text{C} \sim 100^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 100^{\circ}\text{C}$
适用介质: 水、油品、酸、碱类
Applicable medium: Water, oil, acid, alkali



手柄式蝶阀

Handle-type Butterfly Valve

公称通径: DN50~500mm
Nominal diameter: DN50~500mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



蜗轮对夹硬密封蝶阀

Worm Drive On The Hard-seal Butterfly Valve

公称通径: DN40~2600mm
Nominal diameter: DN40~2600mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、空气、油品
Applicable medium: Water, air, oil



蜗轮蝶阀

Worm Wheel Butterfly Valve

公称通径: DN40~1800mm
Nominal diameter: DN40~1800mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



电动蝶阀

Electric Butterfly Valve

公称通径: DN40~1600mm
Nominal diameter: DN40~1600mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标三偏心蝶阀

American Standard Three Eccentric

公称通径: DN11/2"~104"
Nominal diameter: DN11/2"~104"
公称压力: PN150Lb~300Lb
Nominal Pressure: PN150Lb~300Lb
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、热空气、蒸汽、煤气、油品
Applicable medium: Water, air, steam, gas, oil



不锈钢多层次蝶阀

Multi-level Stainless Steel Butterfly Valve

公称通径: DN50~2000mm
Nominal diameter: DN50~2000mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、蒸汽、油品、酸、碱
Applicable medium: Water, steam, oil, acid, alkali



法兰偏心蝶阀

Flange Eccentric Butterfly Valve

公称通径: DN40~2200mm
Nominal diameter: DN40~2200mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: -30℃~120℃
Applicable temperature: -30℃~120℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标蝶阀

American Standard Butterfly

公称通径: DN40~300mm
Nominal diameter: DN40~300mm
公称压力: PN150Lb~300Lb
Nominal Pressure: PN150Lb~300Lb
适用温度: -20℃~425℃
Applicable temperature: -20℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

蝶阀系列 Butterfly Valve Series



气动蝶阀
Pneumatic Butterfly Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、油品
Applicable medium: Water, oil



偏心对焊蝶阀
Three Eccentric Butt Butterfly Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



耐高温蝶阀
High-temperature Butterfly Valve

公称通径: DN50~2000mm
Nominal diameter: DN50~2000mm
公称压力: PN0.6~6.4mm
Nominal Pressure: PN0.6~6.4mm
适用温度: ≤750℃
Applicable temperature: ≤750℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



伸缩蝶阀
Stretch Butterfly Valve

公称通径: DN40~2000mm
Nominal diameter: DN40~2000mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -4.5℃~150℃
Applicable temperature: -4.5℃~150℃
适用介质: 淡水、污水
Applicable medium: Fresh water, sewage



偏心软密封蝶阀
Eccentric Seal Butterfly Valve

公称通径: DN300~3500mm
Nominal diameter: DN300~3500mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -29℃~80℃
Applicable temperature: -29℃~80℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



管网蝶阀
Pipe Network Butterfly Valve

公称通径: DN100~3400mm
Nominal diameter: DN100~3400mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -20℃~150℃
Applicable temperature: -20℃~150℃
适用介质: 水、油品
Applicable medium: Water, oil



信号蝶阀
Signal Butterfly Valve

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、油品
Applicable medium: Water, oil



蜗轮硬密封加长杆蝶阀
Plus Pole Worm Seal Butterfly Valve

公称通径: DN50~500mm
Nominal diameter: DN50~500mm
公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa
适用温度: -30℃~425℃
Applicable temperature: -30℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



手动真空蝶阀
Manual Vacuum Butterfly Valve

公称通径: DN40~250mm
Nominal diameter: DN40~250mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -30℃~120℃
Applicable temperature: -30℃~120℃
适用介质: 纯净空气和非腐蚀性气体
Applicable medium: Pure air and non-corrosive gases



法兰中线衬胶蝶阀
Rubber Lined Butterfly Valve Flange Centerline

公称通径: DN40~1200mm
Nominal diameter: DN40~1200mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -30℃~120℃
Applicable temperature: -30℃~120℃
适用介质: 水、油品
Applicable medium: Water, oil



衬F46对夹蝶阀
Lining F46 Water Butterfly Valve

公称通径: DN40~1200mm
Nominal diameter: DN40~1200mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: -40℃~120℃
Applicable temperature: -40℃~120℃
适用介质: 液体、气体、酸碱类
Applicable medium: Liquid, gas, acids and bases



对夹式蝶阀
Water Type Butterfly Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: -20℃~150℃
Applicable temperature: -20℃~150℃
适用介质: 水、食品类
Applicable medium: Water, food



无销手柄蝶阀
No pin handle butterfly valve

公称通径: DN40~1200mm
Nominal diameter: DN40~1200mm
公称压力: PN1.0~1.6mm
Nominal Pressure: PN1.0~1.6mm
适用温度: -45℃~120℃
Applicable temperature: -45℃~120℃
适用介质: 水、食品类
Applicable medium: Water, food



沟槽信号蝶阀
Groove Signal Butterfly

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: -20℃~100℃
Applicable temperature: -20℃~100℃
适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



气动薄膜调节蝶阀
Pneumatic Diaphragm Control Valve

公称通径: DN50~1000mm
Nominal diameter: DN50~1000mm
公称压力: PN0.6MPa
Nominal Pressure: PN0.6MPa
适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃
适用介质: 悬浮颗粒的流体及浓
Applicable medium: Regulating fluid suspended particles concentration



水电蝶阀成套
Hydropower Butterfly Valve Set

公称通径: DN500~6000mm
Nominal diameter: DN500~6000mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: ≤80℃
Applicable temperature: ≤80℃
适用介质: 水、油品
Applicable medium: Water, oil

蝶阀系列 Butterfly Valve Series



液控缓闭止回蝶阀
Hydraulic Slow-close Butterfly Check Valve

公称口径: DN500~6000mm
Nominal diameter: DN500~6000mm
公称压力: PN0.25~2.5MPa
Nominal Pressure: PN0.25~2.5MPa
适用温度: $\leq 80^{\circ}\text{C}$
Applicable temperature: $\leq 80^{\circ}\text{C}$
适用介质: 水、海水、泥砂水、油品
Applicable medium: Water, seawater, sediment and water, oil



重锤锁闭式液控止回蝶阀
Hammer Locking Hydraulic Check Valve

公称口径: DN500~6000mm
Nominal diameter: DN500~6000mm
公称压力: PN0.6~1.0MPa
Nominal Pressure: PN0.6~1.0MPa
适用温度: $\leq 80^{\circ}\text{C}$
Applicable temperature: $\leq 80^{\circ}\text{C}$
适用介质: 水、海水、黄河水
Applicable medium: Water, sea water, Yellow River



大口径13系列偏心软密封蝶阀
Large Diameter Series 13 Eccentric Seal Butterfly Valve

公称口径: DN200~6000mm
Nominal diameter: DN200~6000mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: -10°C ~ 80°C
Applicable temperature: -10°C ~ 80°C
适用介质: 水、污水
Applicable medium: Water, sewage



快速切断蝶阀
Rapid Shut-off Valve

公称口径: DN200~2000mm
Nominal diameter: DN200~2000mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 空气、煤气和其他气体
Applicable medium: Air, gas and other gases




通风蝶阀
Ventilation Butterfly Valve

公称口径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.05~0.6MPa
Nominal Pressure: PN0.05~0.6MPa
适用温度: -40°C ~ 425°C
Applicable temperature: -40°C ~ 425°C
适用介质: 含尘气体、烟道气
Applicable medium: Dust containing gas, flue gas



大口径电动双偏心煤气蝶阀
Large Caliber Double Eccentric Gas Butterfly Valve

公称口径: DN200~2000mm
Nominal diameter: DN200~2000mm
公称压力: PN2.5MPa
Nominal Pressure: PN2.5MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 含尘气体、空气
Applicable medium: Dust containing gas, air



黄铜氧气蝶阀
Brass Oxygen Butterfly Valve

公称口径: DN50~500mm
Nominal diameter: DN50~500mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: -20°C ~ 150°C
Applicable temperature: -20°C ~ 150°C
适用介质: 水、非腐蚀性液体
Applicable medium: Water, non corrosive liquid



杠杆式密封蝶阀
Lever Seal Butterfly Valve

公称口径: DN50~5300mm
Nominal diameter: DN50~5300mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: 100°C ~ 500°C
Applicable temperature: 100°C ~ 500°C
适用介质: 烟气、空气可燃性气体
Applicable medium: Flue gas, air and combustible gas



遥控浮球阀

Remote Float Ball Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



减压阀

Reducing valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



缓闭止回阀

Slow closing Check Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



流量控制阀

Flow Control Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



泄压阀

Pressure Relief Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



水力电动控制阀

Hydraulic Electric Control Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



水泵控制阀

Pump Control Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



旁通平衡阀

Bypass Balance Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water

水力阀系列 Hydraulic Valve Series



多功能水泵控制阀
Multifunctional Pump Control Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



安全泄压/持压阀
Safety Relief / Holding Pressure Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水、油品
Applicable medium: Water, oil



电动遥控阀
Electric Remote Control Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1~2.5MPa
Nominal Pressure: PN1~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



管阀
Guan Fa

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水、油品
Applicable medium: Water, oil



限流止回阀
Limiting Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



多喷孔减压阀
Multiple Orifice Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN0.6~6.4MPa
Nominal Pressure: PN0.6~6.4MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



高压多功能水泵控制阀
High Pressure Multifunctional Pump Control Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN2.5~6.4MPa
Nominal Pressure: PN2.5~6.4MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



两相流防结垢自适应液力自动阀
Two-phase Flow Scale Adaptive Hydraulic Automatic Control Valve

公称口径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 清水、污水、海水、泥沙
Applicable medium: Fresh water, sewage, seawater, sediment



角型定水位阀

Angle Given Level Valve

公称通径: DN50~1800mm
Nominal diameter: DN50~1800mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 洁净水
Applicable medium: Clean Water



液压水位控制阀

Hydraulic Level Control Valve

公称通径: DN40~350mm
Nominal diameter: DN40~350mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 洁净水
Applicable medium: Clean Water



防污隔断阀

Pollution Cut Off Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水及弱腐蚀性流体
Applicable medium: Water and weak corrosive fluid



过滤防污隔断阀

Filter Pollution Cut Off Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: -10℃~80℃
Applicable temperature: -10℃~80℃
适用介质: 水
Applicable medium: Water



球型止回阀

Ball Check Valve

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水、污水
Applicable medium: Water, sewage



橡胶瓣止回阀

Rubber Disc Check Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水及弱腐蚀性流体
Applicable medium: Water and weak corrosive fluid



Y型过滤器

Y Type Filter

公称通径: DN40~600mm
Nominal diameter: DN40~600mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: 0℃~180℃
Applicable temperature: 0℃~180℃
适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



Y型伸缩过滤器

Y Type Stretch Filter

公称通径: DN40~600mm
Nominal diameter: DN40~600mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: 0℃~180℃
Applicable temperature: 0℃~180℃
适用介质: 水、油品
Applicable medium: Water, oil



静音止回阀

Silent Check Valve

公称通径: DN40 ~ 600mm
Nominal diameter: DN40 ~ 600mm
公称压力: PN1.0 ~ 2.5MPa
Nominal Pressure: PN1.0 ~ 2.5MPa
适用温度: 0°C ~ 80°C
Applicable temperature: 0°C ~ 80°C
适用介质: 水
Applicable medium: Water



消声止回阀

Noise Elimination Check Valve

公称通径: DN40 ~ 600mm
Nominal diameter: DN40 ~ 600mm
公称压力: PN1.0 ~ 2.5MPa
Nominal Pressure: PN1.0 ~ 2.5MPa
适用温度: 0°C ~ 80°C
Applicable temperature: 0°C ~ 80°C
适用介质: 水
Applicable medium: Water



微阻球形止回阀

Micro Resistance Ball Check valve

公称通径: DN350 ~ 600mm
Nominal diameter: DN350 ~ 600mm
公称压力: PN1.0 ~ 2.5MPa
Nominal Pressure: PN1.0 ~ 2.5MPa
适用温度: 0°C ~ 80°C
Applicable temperature: 0°C ~ 80°C
适用介质: 水
Applicable medium: Water



微阻缓闭止回阀

Micro Resistance Slow Close Check Valve

公称通径: DN50 ~ 700mm
Nominal diameter: DN50 ~ 700mm
公称压力: PN1.0 ~ 2.5MPa
Nominal Pressure: PN1.0 ~ 2.5MPa
适用温度: 0°C ~ 80°C
Applicable temperature: 0°C ~ 80°C
适用介质: 水
Applicable medium: Water



蝶型缓冲止回阀

Butterfly cushion Check Valve


公称通径: DN200 ~ 1600mm
Nominal diameter: DN200 ~ 1600mm
公称压力: PN0.6 ~ 2.5MPa
Nominal Pressure: PN0.6 ~ 2.5MPa
适用温度: -10°C ~ 80°C
Applicable temperature: -10°C ~ 80°C
适用介质: 水、油、污水、海水
Applicable medium: Water, oil, sewage, water



蝶型缓闭止回阀

Butterfly Slow Closing Check Valve

公称通径: DN40 ~ 1800mm
Nominal diameter: DN40 ~ 1800mm
公称压力: PN0.6 ~ 4MPa
Nominal Pressure: PN0.6 ~ 4MPa
适用温度: -10°C ~ 80°C
Applicable temperature: -10°C ~ 80°C
适用介质: 水、污水
Applicable medium: Water, sewage



蝶型止回阀

Butterfly Check Valve

公称通径: DN50 ~ 400mm
Nominal diameter: DN50 ~ 400mm
公称压力: PN1.0 ~ 1.6MPa
Nominal Pressure: PN1.0 ~ 1.6MPa
适用温度: 0°C ~ 80°C
Applicable temperature: 0°C ~ 80°C
适用介质: 水
Applicable medium: Water



平衡阀

Balance Valve

公称通径: DN50 ~ 350mm
Nominal diameter: DN50 ~ 350mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: 0°C ~ 100°C
Applicable temperature: 0°C ~ 100°C
适用介质: 水
Applicable medium: Water



数字锁定平衡阀
Digital Lock Balance Valve

公称通径: DN50~350mm
Nominal diameter: DN50~350mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~120℃
Applicable temperature: 0℃~120℃
适用介质: 水
Applicable medium: Water



明杆弹性座封闸阀
Block Letters That Elastic Bars Gate Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: 0℃~120℃
Applicable temperature: 0℃~120℃
适用介质: 水
Applicable medium: Water



暗杆弹性座封闸阀
Dark Bar Resilient Seated Gate Valve

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: 0℃~120℃
Applicable temperature: 0℃~120℃
适用介质: 水
Applicable medium: Water



膜片液压/气动快开排泥阀
Membrane Hydraulic / Pneumatic Quick Squeeze Valve

公称通径: DN100~400mm
Nominal diameter: DN100~400mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水、污水
Applicable medium: Water, sewage



防爆波安全阀
Explosion-proof Safety Valve Wave

公称通径: DN100~400mm
Nominal diameter: DN100~400mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



液压、气动角式快开排泥阀
Hydraulic, Pneumatic Diagonal Quick Squeeze Valve

公称通径: DN80~350mm
Nominal diameter: DN80~350mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水、污水
Applicable medium: Water, sewage



气式水锤吸纳器
Aspirated Water Hammer Absorbing Device

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.6~2.5MPa
Nominal Pressure: PN1.6~2.5MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



自力式压差控制阀
Self-operated Pressure Control Valve

公称通径: DN50~125mm
Nominal diameter: DN50~125mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: 0℃~100℃
Applicable temperature: 0℃~100℃
适用介质: 水
Applicable medium: Water



微量排气阀
Micro Volume Exhaust Valve

公称通径: DN15~25mm
Nominal diameter: DN15~25mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-10^{\circ}\text{C}\sim 120^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C}\sim 120^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



复合式排气阀
Composite Exhaust Valve

公称通径: DN25~500mm
Nominal diameter: DN25~500mm
公称压力: PN1~1.6MPa
Nominal Pressure: PN1~1.6MPa
适用温度: $-10^{\circ}\text{C}\sim 120^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C}\sim 120^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



支管减压阀
Manifold Valve

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.6~2.5MPa
Nominal Pressure: PN1.6~2.5MPa
适用温度: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
Applicable temperature: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



减压阀
Pressure Valve

公称通径: DN15~400mm
Nominal diameter: DN15~400mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、空气
Applicable medium: Water, air



污水排气阀
Sewage Exhaust Valve

公称通径: DN50~250mm
Nominal diameter: DN50~250mm
公称压力: DN50~250mm
Nominal Pressure: DN50~250mm
适用温度: 常温
Applicable temperature: Homiothermy
适用介质: 清水
Applicable medium: Branch water



法兰排气阀
Flange Exhaust Valve

公称通径: DN50~250mm
Nominal diameter: DN50~250mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
Applicable temperature: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



卡箍式鸭嘴阀
Clamp Type Duckbill Valve

公称通径: 50~1200mm
Nominal diameter: 50~1200mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
Applicable temperature: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
适用介质: 水、污水
Applicable medium: Water, sewage



法兰鸭嘴阀
Duckbill Valve Flange

公称通径: DN50~1200mm
Nominal diameter: DN50~1200mm
公称压力: PN0.6~1.6MPa
Nominal Pressure: PN0.6~1.6MPa
适用温度: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
Applicable temperature: $0^{\circ}\text{C}\sim 80^{\circ}\text{C}$
适用介质: 水、污水
Applicable medium: Water, sewage



自由浮球式
Free Ball Float

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



热静力自由浮球式
Thermostatic Free Ball Float

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



杠杆浮球式
Lever Ball Float

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



倒置桶式
Invert Bucket

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN0.01~6.5MPa
Nominal Pressure: PN0.01~6.5MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



双金属温调式
Bimetallic Temperature Tuning

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN0.01~1.6MPa
Nominal Pressure: PN0.01~1.6MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



北京式热动力圆盘式
Beijing Thermal Power Disc

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



杠杆式疏水阀
Leveraged Trap

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.6~10.0MPa
Nominal Pressure: PN1.6~10.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



法兰高压圆盘式
Flange High Voltage Disc

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 550^{\circ}\text{C}$
Applicable temperature: $\leq 550^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam

过滤器系列 Filter Series



T型管道过滤器
T Type Pipe Filter

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



Y型过滤器
Y Type Filter

公称通径: DN40~1600mm
Nominal diameter: DN40~1600mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: $\leq 600^{\circ}\text{C}$
Applicable temperature: $\leq 600^{\circ}\text{C}$
适用介质: 水、蒸汽、酸、碱类
Applicable medium: Water, steam, acid, alkali



蓝式过滤器
Blue Style Filter

公称通径: DN40~600mm
Nominal diameter: DN40~600mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



锥形过滤器
Cone Filter

公称通径: DN20~150mm
Nominal diameter: DN20~150mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



氧气过滤器
Oxygen Filter

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



智能全自动反冲洗过滤器
Intelligent Automatic Backwash Filter

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: $\leq 80^{\circ}\text{C}$
Applicable temperature: $\leq 80^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



桶型自动反冲洗过滤器
Bucket-type Automatic Backwash Filter

公称通径: DN50~800mm
Nominal diameter: DN50~800mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: $\leq 80^{\circ}\text{C}$
Applicable temperature: $\leq 80^{\circ}\text{C}$
适用介质: 水、蒸汽
Applicable medium: Water, steam



双桶切换过滤器
Double Barrel Switching Filter

公称通径: DN100~250mm
Nominal diameter: DN100~250mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



黄铜丝口闸阀
Brass Gate Valve

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



铜丝扣截止阀
Copper Buckle Cut-off Valve

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



黄铜水表丝口闸阀
Brass Wire Gate Valve Water Meter

公称通径: DN15~25mm
Nominal diameter: DN15~25mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



黄铜法兰截止阀
Brass Flange Cut-off Valve

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



黄铜丝口止回阀
Brass Port Valve

公称通径: DN10~50mm
Nominal diameter: DN10~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



黄铜丝口球阀
Brass Wire Ball Valve

公称通径: DN10~50mm
Nominal diameter: DN10~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



黄铜法兰过滤器
Brass Flange Filter

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil



铜丝口Y型过滤器
Copper Y Type Filter

公称通径: DN15~50mm
Nominal diameter: DN15~50mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \leq t \leq 120^{\circ}\text{C}$
适用介质: 冷/热水、汽、油
Applicable medium: Cold/hot water, steam, oil

二通阀系列
Two Valve Series



丝扣气动角座阀
Thread Pneumatic Angle Seat Valve

公称通径: DN15~65mm
Nominal diameter: DN15~65mm
公称压力: PN2.5MPa
Nominal Pressure: PN2.5MPa
适用温度: -20℃~350℃
Applicable temperature: -20℃~350℃
适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



铜系列电磁阀
Copper Series Solenoid Valve

公称通径: DN1/8"~2"
Nominal diameter: DN1/8"~2"
公称压力: PN0~10kgf/cm2
Nominal Pressure: PN0~10kgf/cm2
适用温度: -5℃~120℃
Applicable temperature: -5℃~120℃
适用介质: 空气、(热)水、油、瓦斯
Applicable medium: Air, (hot) water, oil, gas



铜系列电磁阀
Copper Series Solenoid Valve

公称通径: DN1/8"~2"
Nominal diameter: DN1/8"~2"
公称压力: PN0~10kgf/cm2
Nominal Pressure: PN0~10kgf/cm2
适用温度: -5℃~120℃
Applicable temperature: -5℃~120℃
适用介质: 空气、(热)水、油、瓦斯
Applicable medium: Air, (hot) water, oil, gas



(通电关闭)常开型电磁阀
(power Off) Normally Open Solenoid Valve

公称通径: DN1/8"~2"
Nominal diameter: DN1/8"~2"
公称压力: PN0.5~7kgf/cm2
Nominal Pressure: PN0.5~7kgf/cm2
适用温度: -5℃~180℃
Applicable temperature: -5℃~180℃
适用介质: 空气、(热)水、油
Applicable medium: Air, (hot) water, steam, oil



电磁阀
Solenoid Valve

公称通径: DN6~20mm
Nominal diameter: DN6~20mm
公称压力: PN0.6~1.0MPa
Nominal Pressure: PN0.6~1.0MPa
适用温度: ≤155℃
Applicable temperature: ≤155℃
适用介质: 空气、(热)水、油
Applicable medium: Air, (hot) water, oil



不锈钢法兰电磁阀
Stainless Steel Flange Solenoid Valve

公称通径: DN15~150mm
Nominal diameter: DN15~150mm
公称压力: PN1.0~2.5Mpa
Nominal Pressure: PN1.0~2.5Mpa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



电磁阀
Solenoid Valve

公称通径: DN50~250mm
Nominal diameter: DN50~250mm
公称压力: PN0.6~2.5Mpa
Nominal Pressure: PN0.6~2.5Mpa
适用温度: -29℃~425℃
Applicable temperature: -29℃~425℃
适用介质: 煤气、液化气、天然气
Applicable medium: Coal gas, liquefied petroleum gas, natural gas



活塞式常开型系列蒸汽电磁阀
Piston Type Normally Open Type Steam Solenoid Valve

公称通径: DN25~300mm
Nominal diameter: DN25~300mm
公称压力: PN0.05~0.8MPa
Nominal Pressure: PN0.05~0.8MPa
适用温度: 50~220℃
Applicable temperature: 50~220℃
适用介质: 蒸汽、蒸馏水、水
Applicable medium: Steam, water, distilled water



弹簧封闭式安全阀
Spring Closed Safety Valve

公称口径: DN15~200mm
Nominal diameter: DN15~200mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: -40℃~80℃
Applicable temperature: -40℃~80℃
适用介质: 空气、氨、石油气
Applicable medium: Air, ammonia, oil and gas



双联弹簧安全阀
Double Spring Safety Valve

公称口径: DN40~150mm
Nominal diameter: DN40~150mm
公称压力: PN1.6~6.4MPa
Nominal Pressure: PN1.6~6.4MPa
适用温度: ≤350℃
Applicable temperature: ≤350℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



弹簧全启封闭式安全阀
Spring All The Rev Closed Safety Valve

公称口径: DN15~200mm
Nominal diameter: DN15~200mm
公称压力: PN1.6~4.0MPa
Nominal Pressure: PN1.6~4.0MPa
适用温度: -40℃~425℃
Applicable temperature: -40℃~425℃
适用介质: 空气、石油、气、液体
Applicable medium: Air, oil, gas, liquid



自力式温度调节阀
Self Operated Temperature Regulating Valve

公称口径: DN15~200mm
Nominal diameter: DN15~200mm
公称压力: PN1.6~4.6MPa
Nominal Pressure: PN1.6~4.6MPa
适用温度: -40℃~80℃
Applicable temperature: -40℃~80℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



气动精小型套筒调节阀
Pneumatic Fine Small Sieve Regulating Valve

公称口径: DN15~400mm
Nominal diameter: DN15~400mm
公称压力: PN1.0~16.0MPa
Nominal Pressure: PN1.0~16.0MPa
适用温度: -15℃~350℃
Applicable temperature: -15℃~350℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



气动薄膜单座调节阀
Pneumatic Diaphragm Single-seat Regulating Valve

公称口径: DN25~400mm(1"-16")
Nominal diameter: DN25~400mm(1"-16")
公称压力: PN1.0~10MPa(125~1000Lb)
Nominal Pressure: PN1.0~10MPa(125~1000Lb)
适用温度: -50℃~450℃
Applicable temperature: -50℃~450℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



气动调节阀
Pneumatic Control Valve

公称口径: DN20~350mm(3/4"-14")
Nominal diameter: DN20~350mm(3/4"-14")
公称压力: PN1.0~10MPa(125~1000Lb)
Nominal Pressure: PN1.0~10MPa(125~1000Lb)
适用温度: -60℃~250℃
Applicable temperature: -60℃~250℃
适用介质: 水、蒸汽
Applicable medium: Water, steam



氯气专用波纹管调节阀(切断阀)
Special Corrugated Chlorine Pipe Valve (valve)

公称口径: DN20~250mm(3/4"-10")
Nominal diameter: DN20~250mm(3/4"-10")
公称压力: PN1.6~6.4MPa(150~600Lb)
Nominal Pressure: PN1.6~6.4MPa(150~600Lb)
适用温度: -60℃~250℃
Applicable temperature: -60℃~250℃
适用介质: 水、蒸汽
Applicable medium: Water, steam

接头、伸缩节、阻火器系列 Joint, Expansion Joint, Flame Arrester Series



橡胶接头
Rubber Joint

公称通径: DN20~2000mm
Nominal diameter: DN20~2000mm
公称压力: PN1.0~2.0MPa
Nominal Pressure: PN1.0~2.0MPa
适用温度: $-15^{\circ}\text{C} \sim 115^{\circ}\text{C}$
Applicable temperature: $-15^{\circ}\text{C} \sim 115^{\circ}\text{C}$
适用介质: 空气、水、油、酸、碱
Applicable medium: Air, water, oil, acid, alkali



传力接头
Transmission Joint

公称通径: DN25~500mm
Nominal diameter: DN25~500mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



限位伸缩器
Limit Expansion Joints

公称通径: DN50~4000mm
Nominal diameter: DN50~4000mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: $\leq 425^{\circ}\text{C}$
Applicable temperature: $\leq 425^{\circ}\text{C}$
适用介质: 水
Applicable medium: Water



补偿器
Compensator

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



金属软接头
Metal Soft Joint

公称通径: DN8~400mm
Nominal diameter: DN8~400mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 蒸汽、油品
Applicable medium: Steam, oil



法兰金属软管
Flanged Metal Hose

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



防爆阻火呼吸阀
Explosion Fire Breathing Valve

公称通径: DN25~400mm
Nominal diameter: DN25~400mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$
Applicable temperature: $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$
适用介质: 甲苯、油品
Applicable medium: A stupid, oil



阻火呼吸人孔
Manhole Breathing Fire Retardant

公称通径: DN25~350mm
Nominal diameter: DN25~350mm
公称压力: PN0.25~2.5MPa
Nominal Pressure: PN0.25~2.5MPa
适用温度: $-30^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Applicable temperature: $-30^{\circ}\text{C} \sim 150^{\circ}\text{C}$
适用介质: 油、芳烃、硫及空气
Applicable medium: Oil, aromatic, sulfur and air



法兰针型阀
Flange Needle Valve

公称通径: DN3~50mm
Nominal diameter: DN3~50mm
公称压力: PN1.6~70MPa
Nominal Pressure: PN1.6~70MPa
适用温度: -60℃~425℃
Applicable temperature: -60℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



取压截止阀
Take The Pressure Globe Valve

公称通径: DN3~50mm
Nominal diameter: DN3~50mm
公称压力: PN1.6~70MPa
Nominal Pressure: PN1.6~70MPa
适用温度: -60℃~425℃
Applicable temperature: -60℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



针形阀
Needle Valve

公称通径: DN6~25mm
Nominal diameter: DN6~25mm
公称压力: PN1~32MPa
Nominal Pressure: PN1~32MPa
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



内螺纹截止阀
Female Globe Valve

公称通径: DN3~50mm
Nominal diameter: DN3~50mm
公称压力: PN1.6~70MPa
Nominal Pressure: PN1.6~70MPa
适用温度: -60℃~425℃
Applicable temperature: -60℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



针形平衡阀
The Balance Valve Of The Needle-shaped

公称通径: DN6~25mm(1/8"~1")
Nominal diameter: DN6~25mm(1/8"~1")
公称压力: PN1~32MPa(125~2500Lb)
Nominal Pressure: PN1~32MPa(125~2500Lb)
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



D5J11针形多阀组
D5J11 Needle-shaped Manifolds

公称通径: DN6~25mm(1/8"~1")
Nominal diameter: DN6~25mm(1/8"~1")
公称压力: PN1~32MPa(125~2500Lb)
Nominal Pressure: PN1~32MPa(125~2500Lb)
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



针形阀
Needle Valve

公称通径: DN6~25mm
Nominal diameter: DN6~25mm
公称压力: PN1~32MPa
Nominal Pressure: PN1~32MPa
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



针形阀
Needle Valve

公称通径: DN6~25mm
Nominal diameter: DN6~25mm
公称压力: PN1~32MPa
Nominal Pressure: PN1~32MPa
适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

仪表针型阀、液位计、视镜系列
Meter Needle Type Valve, Liquid Level Gauge, Mirror Series



J91型针形阀
J91 Type Needle Valve

公称通径: DN6~25mm
Nominal diameter: DN6~25mm

公称压力: PN1~32MPa
Nominal Pressure: PN1~32MPa

适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃

适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



取压球阀
Take The Pressure Ball Valve

公称通径: DN15~150mm
Nominal diameter: DN15~150mm

材质: 20#, 304, 304L, 316, 316L
Materials: 20#, 304, 304L, 316, 316L



多口计量阀
Metering Valve

公称通径: DN6~25mm
Nominal diameter: DN6~25mm

公称压力: PN1~32MPa
Nominal Pressure: PN1~32MPa

适用温度: -196℃~425℃
Applicable temperature: -196℃~425℃

适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



磁翻板液位计
Magnetic Flap Level Gauge

公称通径: DN20~25mm
Nominal diameter: DN20~25mm

公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa

适用温度: ≤150℃
Applicable temperature: ≤150℃

适用介质: 水
Applicable medium: Water



玻璃管液位计
Glass Tube Liquid Level Gauge

公称通径: DN20~25mm
Nominal diameter: DN20~25mm

公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa

适用温度: ≤150℃
Applicable temperature: ≤150℃

适用介质: 水
Applicable medium: Water



不锈钢直通视镜
Stainless Steel Through Endoscopic

公称通径: DN10~150mm
Nominal diameter: DN10~150mm

公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa

适用温度: -20~232℃
Applicable temperature: -20~232℃

适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



不锈钢玻璃管式视镜
Stainless Steel Tube Type As The Cup

公称通径: DN15~150mm
Nominal diameter: DN15~150mm

公称压力: PN≤0.6Mpa
Nominal Pressure: PN≤0.6Mpa

适用温度: 0~200℃
Applicable temperature: 0~200℃

适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



法兰水流叶轮视镜
Flange Water Impeller Endoscopic

公称通径: DN15~300mm
Nominal diameter: DN15~300mm

公称压力: PN0.6~4.0MPa
Nominal Pressure: PN0.6~4.0MPa

适用温度: 0~195℃
Applicable temperature: 0~195℃

适用介质: 水、油品、气体
Applicable medium: Water, oil, gas



三片式卫生级快装蝶阀
Three Piece Sanitary Quick-install Butterfly Valve

公称通径: DN20~150mm
Nominal diameter: DN20~150mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



卫生级蝶阀
Sanitary Butterfly Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



卫生级球阀
Sanitary Ball Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food




快装止回阀
Quick Check Valve

公称通径: DN15~100mm
Nominal diameter: DN15~100mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



卫生级法兰蝶阀
Sanitary Flange Butterfly Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: PN1.0~4.0MPa
Nominal Pressure: PN1.0~4.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



对夹式蝶阀
Stainless Steel Sanitary Diaphragm Valve

公称通径: DN40~100mm
Nominal diameter: DN40~100mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



卫生级对夹式蝶阀
Sanitary Wafer Butterfly Valve

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN1.6MPa
Nominal Pressure: PN1.6MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



焊接式蝶阀
Welding Type Butterfly Valve

公称通径: DN20~159mm
Nominal diameter: DN20~159mm
公称压力: PN1.0MPa
Nominal Pressure: PN1.0MPa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food

气动、电动执行附件系列
Pneumatic, Electric Actuator Accessories Series



不锈钢气动执行器
Stainless Steel Pneumatic Actuator

适用温度: $-40^{\circ}\text{C} \sim +160^{\circ}\text{C}$
Applicable temperature: $-40^{\circ}\text{C} \sim +160^{\circ}\text{C}$
输出扭矩: $3 \sim 10000\text{Nm}$
Output torque: $3 \sim 10000\text{Nm}$
空气压力: $2 \sim 8\text{bar}$
Air Pressure: $2 \sim 8\text{bar}$




气动执行器
Pneumatic Actuator

适用温度: $-20^{\circ}\text{C} \sim +90^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \sim +90^{\circ}\text{C}$
输出扭矩: $3 \sim 10000\text{Nm}$
Output torque: $3 \sim 10000\text{Nm}$
空气压力: $2 \sim 8\text{bar}$
Air Pressure: $2 \sim 8\text{bar}$



气动执行器
Pneumatic Actuator

适用温度: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Applicable temperature: $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
输出扭矩: $0.4 \sim 0.7\text{MPa}$
Output torque: $0.4 \sim 0.7\text{MPa}$
弹簧复位扭矩: $8.9 \sim 3256$
Spring return torque: $8.9 \sim 3256$



气动执行器
Pneumatic Actuator

气源压力: $0.4 \sim 1.0\text{MPa}$
Air supply pressure: $0.4 \sim 1.0\text{MPa}$
适用温度: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
弹簧扭矩: $230 \sim 27490$
Spring torque: $230 \sim 27490$



气动执行器
Pneumatic Actuator

气源压力: $0.4 \sim 1.0\text{MPa}$
Air supply pressure: $0.4 \sim 1.0\text{MPa}$
适用温度: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
空气压力: $2 \sim 8\text{bar}$
Air Pressure: $2 \sim 8\text{bar}$



电动执行器
Electric Actuator

输出扭矩: $50 \sim 2500\text{Nm}$
Output torque: $50 \sim 2500\text{Nm}$
输出转速: $1 \sim 0.17\text{min}$
Output speed: $1 \sim 0.17\text{min}$



智能电动执行器
Intelligent Electric Actuators

环境温度: $-20 \sim 60^{\circ}\text{C}$
Ambient temperature: $-20 \sim 60^{\circ}\text{C}$
输出扭矩: $100 \sim 5000\text{Nm}$
Output torque: $100 \sim 5000\text{Nm}$



电动执行器
Electric Actuator

适用温度: $-196^{\circ}\text{C} \sim 500^{\circ}\text{C}$
Applicable temperature: $-196^{\circ}\text{C} \sim 500^{\circ}\text{C}$
公称扭矩: $50 \sim 10000$
Nominal torque: $50 \sim 10000$
电机功率: $0.09\text{KW} \sim 15\text{KW}$
Motor power: $0.09\text{KW} \sim 15\text{KW}$



精小型电动执行器
Fine Small Electric Actuator

适用温度: $\leq 60^{\circ}\text{C}$
Applicable temperature: $\leq 60^{\circ}\text{C}$
输出扭矩: 20~2000Nm
Output torque: 20~2000Nm
动作角度: $0 \sim 90^{\circ}$
Action angle: $0 \sim 90^{\circ}$



隔爆型限位开关
Explosion-proof Limit Switch

环境温度: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Ambient temperature: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
接线孔: 2NPT1/2" ~ 2NPT3/4"
Wiring hole: 2NPT1/2" ~ 2NPT3/4"



高耐腐蚀型限位开关
High Corrosion-resistant Type Of Limit Switch

环境温度: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Ambient temperature: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
接线孔: 2NPT1/2" ~ 2NPT3/4"
Wiring hole: 2NPT1/2" ~ 2NPT3/4"



信号开关
A Signal Switch

环境温度: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
Ambient temperature: $-20^{\circ}\text{C} \sim 80^{\circ}\text{C}$
接线孔: 2NPT1/2" ~ 2NPT3/4"
Wiring hole: 2NPT1/2" ~ 2NPT3/4"



智能阀门定位器
Smart Valve Positioner

输入信号: 4 ~ 20mA.DC
Input signal: 4 ~ 20mA.DC
输入阻抗: $250 \pm 25 \Omega$
Input impedance: $250 \pm 25 \Omega$
绝缘电阻: $\geq 100\text{M}\Omega$
Insulation resistance: $\geq 100\text{M}\Omega$



二位五通电磁阀
Two Five-way Solenoid Valve

使用压力范围: 0.15~0.8Mpa
Pressure range: 0.15~0.8Mpa
适用介质: 空气
Applicable medium: Air
适用温度: $-20 \sim 70^{\circ}\text{C}$
Temperature range: $-20 \sim 70^{\circ}\text{C}$
作动方式: 先导式
Actuation mode: Pilot



空气过滤减压阀
Air Filter Regulator Valve

最大进口压力: 250PSI
Maximum Inlet Pressure: 250PSI
出口压力: 0~125PSI
Export Pressure: 0~125PSI
连接尺寸: 1/4 inch
Connection Size: 1/4 inch



活塞式电磁阀
Piston Solenoid Valves

额定温度: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$
Rated temperature: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$
工作压力: 2.4~8.3bar
Working pressure: 2.4~8.3bar
流量: $\text{Cv}=0.8 \sim \text{Cv} > 1.1$
Flow: $\text{Cv}=0.8 \sim \text{Cv} > 1.1$

船用阀门系列
Marine valve series



法兰铸铁闸阀
Flange Cast Iron Gate Valve

公称通径: DN50 ~ 500mm
Nominal diameter: DN50 ~ 500mm
公称压力: PN0.25 ~ 0.6MPa
Nominal Pressure: PN0.25 ~ 0.6MPa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



法兰铸铁止回阀
Cast Iron Flanged Lift Check Valve

公称通径: DN50 ~ 150mm
Nominal diameter: DN50 ~ 150mm
公称压力: PN0.6 ~ 1.6Mpa
Nominal Pressure: PN0.6 ~ 1.6Mpa
适用温度: $\leq 220^{\circ}\text{C}$
Applicable temperature: $\leq 220^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



法兰铸铁直角截止阀
Flange Cast Iron Angle Valve

公称通径: DN15 ~ 100mm
Nominal diameter: DN15 ~ 100mm
公称压力: PN0.6 ~ 1.0Mpa
Nominal Pressure: PN0.6 ~ 1.0Mpa
适用温度: $\leq 220^{\circ}\text{C}$
Applicable temperature: $\leq 220^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



船用呼吸阀
Marine Breathing Valve

公称通径: DN6 ~ 600mm
Nominal diameter: DN6 ~ 600mm
公称压力: PN1.0 ~ 6.4Mpa
Nominal Pressure: PN1.0 ~ 6.4Mpa
适用温度: $\leq 230^{\circ}\text{C}$
Applicable temperature: $\leq 230^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



法兰青铜截止阀
Bronze Flanged Sea Stop Valves

公称通径: DN20 ~ 150mm
Nominal diameter: DN20 ~ 150mm
公称压力: PN0.6 ~ 10.0Mpa
Nominal Pressure: PN0.6 ~ 10.0Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



青铜吸入通海阀
Bronze Suction Sea Valves

公称通径: DN15 ~ 150mm
Nominal diameter: DN15 ~ 150mm
公称压力: PN0.25 ~ 1.6Mpa
Nominal Pressure: PN0.25 ~ 1.6Mpa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



法兰铸铁直角截止阀
Flange Cast Iron Angle Valve

公称通径: DN50 ~ 200mm
Nominal diameter: DN50 ~ 200mm
公称压力: PN0.6 ~ 1.0Mpa
Nominal Pressure: PN0.6 ~ 1.0Mpa
适用温度: $\leq 230^{\circ}\text{C}$
Applicable temperature: $\leq 230^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



船用阀
Valve For Ship

公称通径: DN15 ~ 50mm
Nominal diameter: DN15 ~ 50mm
公称压力: PN0.6 ~ 1.0Mpa
Nominal Pressure: PN0.6 ~ 1.0Mpa
适用温度: $\leq 220^{\circ}\text{C}$
Applicable temperature: $\leq 220^{\circ}\text{C}$
适用介质: 海水、淡水、滑油
Applicable medium: Sea water, fresh water, oil



不锈钢三通旋塞阀
Stainless Steel Plug Valves Three

公称通径: DN50~300mm
Nominal diameter: DN50~300mm
公称压力: PN1.0Mpa
Nominal Pressure: PN1.0Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 水、油品、煤气
Applicable medium: Water, oil, gas



不锈钢内螺纹三通旋塞阀
Stainless Steel Thread Plug Valves Three

公称通径: DN20~300mm
Nominal diameter: DN20~300mm
公称压力: PN1.0Mpa
Nominal Pressure: PN1.0Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 水、污水、油品
Applicable medium: Water, sewage, oil



软密封卡套旋塞阀
Soft Sealing Sleeve Plug Valve

公称通径: DN150~900mm
Nominal diameter: DN150~900mm
公称压力: PN0.6~6.4Mpa
Nominal Pressure: PN0.6~6.4Mpa
适用温度: $-29^{\circ}\text{C} \sim 180^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 180^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



轨道式旋塞阀
Orbit Plug Valve

公称通径: DN150~900mm
Nominal diameter: DN150~900mm
公称压力: PN1.6~32.0mpa
Nominal Pressure: PN1.6~32.0mpa
适用温度: $-29^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 150^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



二通保温旋塞阀
Two Insulation Plug Valve

公称通径: DN20~300mm
Nominal diameter: DN20~300mm
公称压力: PN1.0Mpa
Nominal Pressure: PN1.0Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 水、污水、油品
Applicable medium: Water, sewage, oil




衬氟旋塞阀
Fluorine Lining Valve

公称通径: DN20~250mm
Nominal diameter: DN20~250mm
公称压力: PN0.1~2.5mpa
Nominal Pressure: PN0.1~2.5mpa
适用温度: $-29^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Applicable temperature: $-29^{\circ}\text{C} \sim 150^{\circ}\text{C}$
适用介质: 水、油品
Applicable medium: Water, oil



法兰提升式硬密封旋塞阀
Flange Lifting Type Hard Sealing Plug Valve

公称通径: DN15~350mm
Nominal diameter: DN15~350mm
公称压力: PN0.1~16.0Mpa
Nominal Pressure: PN0.1~16.0Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil



美标卡套式旋塞阀
American Standard Sleeve Type Plug Valve

公称通径: DN2"~12"
Nominal diameter: DN2"~12"
公称压力: PN150Lb~900Lb
Nominal Pressure: PN150Lb~900Lb
适用温度: $\leq 180^{\circ}\text{C}$
Applicable temperature: $\leq 180^{\circ}\text{C}$
适用介质: 水、蒸汽、油品
Applicable medium: Water, steam, oil

隔膜阀系列 Diaphragm Valve Series



衬氟隔膜阀
Fluorine Lined Diaphragm Valve

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN0.6~1.6Mpa
Nominal Pressure: PN0.6~1.6Mpa
适用温度: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



不锈钢卫生级隔膜阀
Stainless Steel Sanitary Diaphragm Valve

公称通径: DN40~500mm
Nominal diameter: DN40~500mm
公称压力: PN1.0~4.0Mpa
Nominal Pressure: PN1.0~4.0Mpa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 水、食品类
Applicable medium: Water, food



塑料隔膜阀
Plastic Diaphragm Valve

公称通径: DN50~600mm
Nominal diameter: DN50~600mm
公称压力: PN0.2~1.0Mpa
Nominal Pressure: PN0.2~1.0Mpa
适用温度: $-14^{\circ}\text{C} \sim 100^{\circ}\text{C}$
Applicable temperature: $-14^{\circ}\text{C} \sim 100^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



双动型隔膜阀
Double Acting Diaphragm Valve

公称通径: DN25~100mm
Nominal diameter: DN25~100mm
公称压力: PN0.6~6.4Mpa
Nominal Pressure: PN0.6~6.4Mpa
适用温度: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



三通衬胶隔膜阀
Three Rubber Lined Diaphragm Valve

公称通径: DN25~125mm
Nominal diameter: DN25~125mm
公称压力: PN0.6~6.4Mpa
Nominal Pressure: PN0.6~6.4Mpa
适用温度: $\leq 85^{\circ}\text{C}$
Applicable temperature: $\leq 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



直流式衬胶隔膜阀
Dc Rubber Lined Diaphragm Valve

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN0.6~1.6mpa
Nominal Pressure: PN0.6~1.6mpa
适用温度: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium




气动隔膜阀
Pneumatic Diaphragm Valve

公称通径: DN20~200mm
Nominal diameter: DN20~200mm
公称压力: PN1.6~32.0mpa
Nominal Pressure: PN1.6~32.0mpa
适用温度: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



衬胶隔膜阀
Rubber Lined Diaphragm Valve

公称通径: DN15~300mm
Nominal diameter: DN15~300mm
公称压力: PN0.6~1.6mpa
Nominal Pressure: PN0.6~1.6mpa
适用温度: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Applicable temperature: $-10^{\circ}\text{C} \sim 85^{\circ}\text{C}$
适用介质: 强腐蚀性介质
Applicable medium: Strong corrosive medium



法兰式水流指示器
Flange Type Water Flow Indicator

额定工作压力: 1.2MPa
Nominal working pressure: 1.2MPa
动作流量: 37.5L/min
Operation flow: 37.5L/min
延时范围(s): 2~90
Range of time delay (s): 2~90
电源电压: DC-24V/0.75A
Supply voltage: DC-24V/0.75A



湿式报警阀装置
Wet Alarm Valve Device

额定工作压力: 1.2MPa
Nominal working pressure: 1.2MPa
动作流量: 20~170L/min
Operation flow: 20~170L/min
水力摩阻损失: <0.02MPa
Hydraulic friction loss: <0.02MPa
使用环境温度: 4℃~70℃
Use environment temperature: 4℃~70℃



雨淋阀
Deluge Valve

额定工作压力: 1.2MPa
Nominal working pressure: 1.2MPa
压力开关参数: DC24V 1.5A
Pressure switch parameter: DC24V 1.5A
水力摩阻损失: <0.02MPa
Hydraulic friction loss: <0.02MPa
使用环境温度: ≤5℃
Use environment temperature: ≤5℃



预作用报警阀装置
Valve Device Of Alarm Pretreatment

额定工作压力: 1.2MPa
Nominal working pressure: 1.2MPa
动作流量: 20~170L/min
Operation flow: 20~170L/min
水力摩阻损失: <0.02MPa
Hydraulic friction loss: <0.02MPa
使用环境温度: 4℃~70℃
Use environment temperature: 4℃~70℃



干式报警阀
Dry-type Alarm Valve

额定工作压力: 1.2MPa
Nominal working pressure: 1.2MPa
密封试验压力: 2.4MPa
Seal test pressure: 2.4MPa
强度试验压力: 4.8MPa
Strength test pressure: 4.8MPa
使用环境温度: 4℃~70℃
Use environment temperature: 4℃~70℃



地上式接合器
The Ground Bonder

公称通径: DN100~150mm
Nominal diameter: DN100~150mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water



地下式接合器
Underground Bonder

公称通径: DN100~150mm
Nominal diameter: DN100~150mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: 0℃~80℃
Applicable temperature: 0℃~80℃
适用介质: 水
Applicable medium: Water




马鞍式水流指示器
Saddle Type Water Flow Indicator

公称通径: DN100~150mm
Nominal diameter: DN100~150mm
公称压力: PN1.0~1.6MPa
Nominal Pressure: PN1.0~1.6MPa
适用温度: -40℃~600℃
Applicable temperature: -40℃~600℃
适用介质: 水
Applicable medium: Water



电动盲板阀
Electric Blind Plate Valve

公称通径: DN300 ~ 2000mm
Nominal diameter: DN300 ~ 2000mm
公称压力: PN0.5~2.5MPa
Nominal Pressure: PN0.5~2.5MPa
适用温度: 120℃~300℃
Applicable temperature: 120℃~300℃
适用介质: 煤气及有毒、有害、易燃气体
Applicable medium: Gas and toxic, hazardous, flammable gas



链轮式盲板阀
Chain Wheel Type Blind Plate Valve

公称通径: DN300~1400mm
Nominal diameter: DN300~1400mm
公称压力: PN0.5~2.5MPa
Nominal Pressure: PN0.5~2.5MPa
适用温度: 120℃~300℃
Applicable temperature: 120℃~300℃
适用介质: 煤气及有毒、有害、易燃气体
Applicable medium: Gas and toxic, hazardous, flammable gas



手动眼镜阀
Manual Valve

公称通径: DN100 ~ 1200mm
Nominal diameter: DN100 ~ 1200mm
公称压力: PN0.5~2.5MPa
Nominal Pressure: PN0.5~2.5MPa
适用温度: ≤300℃
Applicable temperature: ≤300℃
适用介质: 煤气及有毒、有害、易燃气体
Applicable medium: Gas and toxic, hazardous, flammable gas



封闭式插板阀
Closed Type Board Plug Valve

公称通径: DN400~2800mm
Nominal diameter: DN400~2800mm
公称压力: PN0.5~2.5MPa
Nominal Pressure: PN0.5~2.5MPa
适用温度: ≤120℃~450℃
Applicable temperature: ≤120℃~450℃
适用介质: 煤气及有毒、有害、易燃气体
Applicable medium: Gas and toxic, hazardous, flammable gas



炉顶放散阀
Bleeding Valve

公称通径: DN200 ~ 550mm
Nominal diameter: DN200 ~ 550mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: ≤300℃
Applicable temperature: ≤300℃
适用介质: 空气、尘气、煤气
Applicable medium: Air, gas, coal dust



旁通阀
Bypass Valve

公称通径: DN400 ~ 1600mm
Nominal diameter: DN400 ~ 1600mm
公称压力: PN1.0~2.5MPa
Nominal Pressure: PN1.0~2.5MPa
适用温度: ≤150℃
Applicable temperature: ≤150℃
适用介质: 煤气、含尘气体冷热气
Applicable medium: Gas, gas dust of cold and hot air



防爆阀
Explosion-proof Valve

公称通径: DN200 ~ 900mm
Nominal diameter: DN200 ~ 900mm
公称压力: PN1.0
Nominal Pressure: PN1.0
适用温度: ≤300℃
Applicable temperature: ≤300℃
适用介质: 压缩易爆气体
Applicable medium: Compression and explosive gas



均压放散阀
Pressure Relief Valve

公称通径: DN100 ~ 500mm
Nominal diameter: DN100 ~ 500mm
公称压力: PN0.5~2.5MPa
Nominal Pressure: PN0.5~2.5MPa
适用温度: ≤200℃
Applicable temperature: ≤200℃
适用介质: 煤气
Applicable medium: Gas



自力式煤气安全切断阀
Self-acting Gas Safety Shut-off Valve

公称通径: DN50 ~ 1800mm
Nominal diameter: DN50 ~ 1800mm
公称压力: PN2.5MPa
Nominal Pressure: PN2.5MPa
适用温度: $\leq 450^{\circ}\text{C}$
Applicable temperature: $\leq 450^{\circ}\text{C}$
适用介质: 空气、煤气和其他气体
Applicable medium: Air, gas and other gases



电动圆型百叶阀
Electric Circular Shutter Valve

公称通径: DN500 ~ 3750mm
Nominal diameter: DN500 ~ 3750mm
公称压力: PN0.5MPa
Nominal Pressure: PN0.5MPa
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 含尘气体、空气、烟气
Applicable medium: Dust containing gas, air, flue gas



电动双层卸灰阀
Electric Double-layer Unloading Valve

公称通径: DN150 ~ 700mm
Nominal diameter: DN150 ~ 700mm
公称压力: 1.5 ~ 250m3/h
Nominal Pressure: 1.5 ~ 250m3/h
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 固体小颗粒、粉体物料
Applicable medium: Small solid particles, powder materials



智能式双层卸灰阀
Intelligent Type Double-layer Unloading Valve

公称通径: DN150 ~ 700mm
Nominal diameter: DN150 ~ 700mm
公称压力: 1.5 ~ 300m3/h
Nominal Pressure: 1.5 ~ 300m3/h
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 固体小颗粒、粉体物料
Applicable medium: Small solid particles, powder materials



气动卸灰球阀
Pneumatic Ash Unloading Valve

公称通径: DN200 ~ 600mm
Nominal diameter: DN200 ~ 600mm
公称压力: PN6MPa
Nominal Pressure: PN6MPa
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 煤粉及其它粉状物料
Applicable medium: Coal powder and other powder materials



不锈钢闸门
Stainless Steel Gate

公称通径: DN200 ~ 4000mm
Nominal diameter: DN200 ~ 4000mm
适用介质: 污水、海水、清水
Applicable medium: Sewage, sea water, fresh water



正、侧三通溜子
Positive, Side Three Valve

公称通径: DN200 ~ 710mm
Nominal diameter: DN200 ~ 710mm
适用温度: $\leq 350^{\circ}\text{C}$
Applicable temperature: $\leq 350^{\circ}\text{C}$
适用介质: 粉状物料、固体晶粒
Applicable medium: Powdery material, solid grain



齿条式冷风阀
Rack Type Air Valve

公称通径: DN400 ~ 1400mm
Nominal diameter: DN400 ~ 1400mm
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 空气、煤气和其他气体
Applicable medium: Air, gas and other gases



插板阀
Flapper Valve

公称通径: DN200 ~ 2000mm
Nominal diameter: DN200 ~ 2000mm
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 粉体、晶体粒、颗粒料
Applicable medium: Powder, crystal grains, granules



圆型插板阀
Round Type Board Plug Valve

公称通径: DN80 ~ 600mm
Nominal diameter: DN80 ~ 600mm
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 粉体、晶体粒、颗粒料
Applicable medium: Powder, crystal grains, granules



圆形闸门
Circular Gates

公称通径: DN200 ~ 2500mm
Nominal diameter: DN200 ~ 2500mm
适用介质: 污水、海水、清水
Applicable medium: Sewage, sea water, fresh water



手电动两用启闭机
Manual And Electric Hoist

规格: 45 ~ 500
Specification: 45 ~ 500
启闭力: 4 ~ 25T
Opening and closing force: 4 ~ 25T
电机功率: 1.1 ~ 7.5KW
Motor power: 1.1 ~ 7.5KW




可调堰门
Adjustable Weir

公称通径: DN600 ~ 5000mm
Nominal diameter: DN600 ~ 5000mm
适用介质: 污水、海水、清水
Applicable medium: Sewage, sea water, fresh water



滑板阀
Slide Valve

公称通径: DN50 ~ 700mm
Nominal diameter: DN50 ~ 700mm
适用介质: 污水、海水、清水
Applicable medium: Sewage, sea water, fresh water



除尘放散阀
Dust Discharge Valve

公称通径: DN150 ~ 600mm
Nominal diameter: DN150 ~ 600mm
公称压力: PN1.0 ~ 2.5MPa
Nominal Pressure: PN1.0 ~ 2.5MPa
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 空气、煤气和其他气体
Applicable medium: Air, gas and other gases



冶金泄爆阀
Metallurgical Vent Valve

公称通径: DN300 ~ 1500mm
Nominal diameter: DN300 ~ 1500mm
公称压力: PN0.1Mpa
Nominal Pressure: PN0.1Mpa
适用温度: $\leq 200^{\circ}\text{C}$
Applicable temperature: $\leq 200^{\circ}\text{C}$
适用介质: 压缩易爆气体
Applicable medium: Compression and explosive gas



热风阀
Hot-blast Valve

公称通径: DN500 ~ 1300mm
Nominal diameter: DN500 ~ 1300mm
公称压力: PN0.4Mpa
Nominal Pressure: PN0.4Mpa
适用温度: $\leq 1350^{\circ}\text{C}$
Applicable temperature: $\leq 1350^{\circ}\text{C}$
适用介质: 含尘气体、高温气体
Applicable medium: Dust containing gas, high temperature gas



高炉煤气调压阀组
Blast Furnace Gas Pressure Regulating Valve

公称通径: DN1220 ~ 2700mm
Nominal diameter: DN1220 ~ 2700mm
公称压力: PN1.0~2.5Mpa
Nominal Pressure: PN1.0~2.5Mpa
适用温度: $\leq 250^{\circ}\text{C}$
Applicable temperature: $\leq 250^{\circ}\text{C}$
适用介质: 高炉煤气
Applicable medium: Blast-furnace gas




液动角型废气阀
Hydraulic Angle Type Exhaust Valve

公称通径: DN150 ~ 400mm
Nominal diameter: DN150 ~ 400mm
公称压力: PN3Mpa
Nominal Pressure: PN3Mpa
适用温度: $\leq 300^{\circ}\text{C}$
Applicable temperature: $\leq 300^{\circ}\text{C}$
适用介质: 废气、烟气、热空气
Applicable medium: Waste gas, flue gas, hot air



管接放料阀
Pipe The Discharge Valve

公称通径: DN25~300mm
Nominal diameter: DN25~300mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: $-20^{\circ}\text{C} \sim 425^{\circ}\text{C}$
Applicable temperature: $-20^{\circ}\text{C} \sim 425^{\circ}\text{C}$
适用介质: 油品、酸类、腐蚀性介质
Applicable medium: Oil, acids, corrosive medium



烟道阀
Chimney Valve

公称通径: DN500 ~ 1300mm
Nominal diameter: DN500 ~ 1300mm
公称压力: PN1Mpa
Nominal Pressure: PN1Mpa
适用温度: $\leq 1350^{\circ}\text{C}$
Applicable temperature: $\leq 1350^{\circ}\text{C}$
适用介质: 含尘气体、高温气体
Applicable medium: Dust containing gas, high temperature gas



气动保温放料阀
Pneumatic Thermal Discharge Valve

公称通径: DN25~250mm
Nominal diameter: DN25~250mm
公称压力: PN0.6 ~ 2.5MPa
Nominal Pressure: PN0.6 ~ 2.5MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、丙酮、酒精
Applicable medium: Water, acetone, alcohol



上展式放料阀
On The Expansion Of The Discharge Valve

公称通径: DN25~250mm
Nominal diameter: DN25~250mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、丙酮、酒精
Applicable medium: Water, acetone, alcohol



下展式放料阀
Under The Expansion Of The Discharge Valve

公称通径: DN25~250mm
Nominal diameter: DN25~250mm
公称压力: PN0.6~2.5MPa
Nominal Pressure: PN0.6~2.5MPa
适用温度: $\leq 150^{\circ}\text{C}$
Applicable temperature: $\leq 150^{\circ}\text{C}$
适用介质: 水、丙酮、酒精
Applicable medium: Water, acetone, alcohol